

Finlandia FIN / FLB Sauna Heater Specs

Model	Input	Min. height	Floor area		Sauna Room		Min. spacing from adjacent surfaces inches
			Min. Sq.Ft	Max. Sq.Ft	Min. Cu.Ft	Max. Cu.Ft	
KIP-30-B/W FLB/FIN-30	3.0	6' 2"	10	20	84	130	3"
KIP-45-B/W FLB/FIN-45	4.5	6' 2"	16	30	100	210	3"
KIP-60-B/W FLB/FIN-60	6.0	6' 2"	28	40	170	300	4"
KIP-80-B/W FLB/FIN-80	8.0	6' 2"	40	65	250	425	5"

SAUNA HEATER (240 V) WITH BUILT IN CONTROLS					
Model	Watts	Amps	Voltage	Phase	Wire size
KIP-30-B1 FLB-30	3000	12,5	240	1	12
KIP-45-B1 FLB-45	4500	18,8	240	1	10
KIP-60-B1 FLB-60	6000	25,0	240	1	10
KIP-80-B1 FLB-80	8000	33,3	240	1	8

SAUNA HEATER (208 V) WITH BUILT IN CONTROLS					
Model	Watts	Amps	Voltage	Phase	Wire size
KIP-30-B3 FLB-30-3	3000	8,3	208	3	14
KIP-45-B3 FLB-45-3	4500	12,5	208	3	14
KIP-60-B3 FLB-60-3	6000	16,7	208	3	12
KIP-80-B3 FLB-80-3	8000	22,2	208	3	10